



D and DA Valves

Product Bulletin

FISHER

[Tables](#) [Figures](#) [Coefficients](#) [Print Version](#) [Collapse](#) [Expand](#)

Design D and DA Control Valves

D and DA Valves Description

Design D and DA single-port, high-pressure valves (figure 1) are widely used in oil and gas production industries. These valves are especially useful for either throttling or on/off control of liquids or gases which are gritty, sticky, or which have a tendency to build up on internal valve parts. The Design DA valve is also useful in angle piping or other applications where a self-draining valve is desired.

Unless otherwise noted, all NACE references are to NACE MR0175-2002.

Note

Neither Emerson, Emerson Process Management, nor any of their affiliated entities assumes responsibility for the selection, use and maintenance of any product. Responsibility for the selection, use, and maintenance of any product remains with the purchaser and end-user.

[Close Section Above](#)**Features**

- **Heavy-Duty Construction**—Massive guiding (figure 2) positively aligns the valve plug in the seat ring for high pressure drop applications. The screwed-in seat ring completely encloses the seat ring gasket.
- **Easy Maintenance**—Screwed bonnet/body joint allows repair or maintenance with a minimum of tools.
- **Severe Service Capability**—Valve is available with VTC (ceramic) trim for service in very erosive applications. The valve plug is also available with a tungsten carbide tip and the seat ring can be fitted with a full-bore tungsten carbide insert for erosive service.
- **Meets Variety of Specifications**—Valve body and end connection constructions are available for API as well as ASME standards.
- **NACE Trim Standard**—NACE trim and bolting materials are standard for all applications. These materials comply with the requirements of NACE MR0175-2002.

[Close Section Above](#)**Installation**

Valve orientation of the Design D and DA does not affect operation, but to facilitate changing trim parts, the valve stem should be vertical with the actuator above the valve. Proper flow direction is indicated by the arrow on the valve. Dimensions are shown in figures 3 and 4.

[Close Section Above](#)**Ordering Information**

When ordering, specify:

Application

1. Type of application
 - a. Throttling or on-off
 - b. Reducing or relief
2. Controlled fluid (include chemical analysis of fluid, if possible)
3. Specific gravity of controlled fluid
4. Fluid temperature
5. Range of flowing inlet pressure
6. Pressure drops
 - a. Range of flowing pressure drops
 - b. Maximum at shutoff
7. Flow rates
 - a. Minimum controlled flow
 - b. Normal flow
 - c. Maximum flow
8. Maximum permissible noise level, if critical
9. Shutoff classification required
10. Line size and schedule

Valve

Refer to the specifications. Review the description for each specification. Indicate the desired choice whenever there is a selection (■) to be made. Always indicate the valve body design being ordered as identified in the available configuration specification.

Actuator and Accessories

Refer to separate bulletins covering actuators and accessories for ordering information.

[Close Section Above](#)

Specifications

Available Configurations

Design D: Globe valve with screwed-on bonnet, unbalanced post-guided valve plug, screwed-in seat ring, metal seat construction, and push-down-to-close valve plug action

Design DA: Same as Design D except in angle configuration (figure 2)

Valve Sizes and End Connections⁽¹⁾

See table 1

Maximum Inlet Pressures and Temperatures⁽¹⁾⁽²⁾

See table 2

Maximum Allowable Pressure Drops⁽²⁾

Flow up: Capable of full rated pressure drops

Flow down: See table 3 for pressure drop limits for ceramic trim

Shutoff Classification per ANSI/FCI 70-2 and IEC 60534-4

Standard: Class IV leakage

Optional: Class V

Material Temperature Capabilities

-46 to 232Å°C (-50 to 450Å°F)

Construction Materials

Body, Bonnet, and Trim: See table 4.

Packing:

Standard: ■Single or ■double PTFE V-ring packing for pressure service

Optional: Double PTFE/Composition

Standard Gaskets: S31600 (316 SST)

Flow Characteristic

Equal percentage

Flow Direction (see figure 2)

Design D: Flow up (through seat ring and past valve plug)

Design DA: ■Flow up (through seat ring and past valve plug) or ■flow down (past valve plug and through seat ring)

Flow Coefficients and Noise Level Prediction

See table 5 and the section titled Coefficients in this bulletin or Fisher® Catalog 12

Port, Yoke Boss, Stem Diameters, and Rated Travels

See table 6

Approximate Weights

NPS 1: 34 kg (75 pounds)

NPS 2: 45 kg (100 pounds)

Options

■Lubricator/isolating valve ■VTC (ceramic) Trim with equal percentage characteristic (not available with Micro-Flute trim) ■Tungsten Carbide trim (not available with Micro-Flute trim)

1. EN (or other) ratings and end connections can usually be supplied; consult your Emerson Process Management sales office.

2. The pressure/temperature limits in this bulletin and in any applicable standard limitations should not be exceeded.

Note

Neither Emerson, Emerson Process Management, nor any of their affiliated entities assumes responsibility for the selection, use and maintenance of any product. Responsibility for the selection, use, and maintenance of any product remains with the purchaser and end-user.

[Close Section Above](#)

Table

Table 1. Valve Sizes, Port Diameters, and End Connections

VALVE SIZE, NPS	PORT DIAMETER (INCHES)	SCREWED VALVE BODIES				FLANGED VALVE BODIES			
		3600 psi	6000 psi	9000 psi (WCC Steel Design DA Only)	10,000 psi (Except WCC Steel Design DA)	ASME			API
						CL150 through CL600	CL900 and CL1500	CL2500	10,000 lb. Specs A, B, and C
1	0.25, 0.375, 0.5, 0.75	X ⁽¹⁾	X	---	---	---	X	X	---
2	0.25, 0.375, 0.5, 0.75, 1, 1.25	X	X	X	X	X	X	X	X

1. 'X' indicates available construction.

Close Section Above

Table 2. Rated Inlet Pressures and Temperatures

VALVE SIZE, NPS	TYPE	PRESSURE RATING OR COLD WORKING PRESSURE LIMIT	PRESSURE ⁽¹⁾		TEMPERATURE	
			bar	psi	°C	°F
1 or 2	Screwed	CL900 and 1500	259 236	3750 3425	38 232	100 450
		CL2500	431 394	6250 5710	38 232	100 450
		9000	621	9000	38	100
		10,000	689	10,000	38	100
1 or 2	Flanged	CL150	20.0 12.8	290 185	38 232	100 450
		CL300	51.7 47.2	750 685	38 232	100 450
		CL600	103.4 94.5	1500 1370	38 232	100 450
		CL900 and 1500	259 236	3750 3425	38 232	100 450
		CL2500	431 394	6250 5710	38 232	100 450
		API 10,000	689 689 689	Spec A 10,000 Spec B 10,000 Spec C 10,000	121 38 121	250 100 250

1. LCC steel body per ASME B16.34 except C5 steel for all API bodies.

Close Section Above

Table 3. Flow Down Pressure Drop Limits - Ceramic Trim Only

VALVE SIZE, NPS	SEAT RING DIAMETER, mm (INCHES)					
	6.4 (0.25)	9.5 (0.375)	12.7 (0.5)	19.1 (0.75)	25.4 (1)	31.8 (1.25)
	Pressure Drop, bar					
1	414	414	414	193	---	---
2	689	689	689	462	262	165
	Pressure Drop, psi					
1	6000	6000	6000	2800	---	---

2	10,000	10,000	10,000	6700	3800	2400
---	--------	--------	--------	------	------	------

[Close Section Above](#)

Table 4. Materials for Standard Trim Constructions

VALVE MATERIAL	BONNET MATERIAL	PLUG AND SEAT RING	VALVE STEM
LCC	LF2	S31600 (316 stainless steel) hard faced with CoCr-A (Alloy 6)	S20910
WCC			

[Close Section Above](#)

Table 5. Flow Coefficient (C_v at Maximum Valve Plug Travel)

VALVE SIZE, NPS	PORT DIAMETER, mm (INCHES)	EQUAL PERCENTAGE DESIGN D	
		Flow Up	Flow Down
1	6.4 (0.25)	1.66	3.21
	9.5 (0.375)	4.03	7.06
	12.7 (0.5)	6.51	11.2
	19.1 (0.75)	12.3	16.8
2	6.4 (0.25)	1.66	3.21
	9.5 (0.375)	4.03	7.06
	12.7 (0.5)	6.82	12.1
	19.1 (0.75)	14.1	21.2
	25.4 (1)	23.7	31.8
	31.8 (1.25)	34.5	44.9

[Close Section Above](#)

Table 6. Port, Yoke Boss, Stem Diameters, and Rated Travel Specifications in mm (Inches)

VALVE SIZE, NPS	PORT DIAMETER	STANDARD			OPTIONAL		
		Yoke Boss Diameter	Stem Diameter	Rated Travel	Yoke Boss Diameter	Stem Diameter	Rated Travel
1	6.4 (0.25)	54 (2-1/8)	9.5 (3/8)	19.1 (0.75)	71 (2-13/16)	12.7 (1/2)	19.1 (0.75)
	90 (3-9/16)				19.1 (3/4)	19.1 (0.75)	
2	6.4 (0.25)	71 (2-13/16)	12.7 (1/2)	19.1 (0.75)	90 (3-9/16)	19.1 (3/4)	19.1 (0.75)
	9.5 (0.375)						
	12.7 (0.5)						
	19.1 (0.75)						
	25.4 (1)						
31.8 (1.25)							

[Close Section Above](#)

Table 7. Design D Dimensions

FLANGED VALVE SIZE, NPS	ASME									D—All Ratings		
	CL150		CL300			CL600						
	A-Raised Face	G	A		G	A		G	Stem Size			
			Raised Face	Ring-Type Joint		Raised Face	Ring-Type Joint		9.5 (3/8)	12.7 (1/2)	19.1 (3/4)	
mm												
1	206	46	219	232	46	232	232	46	173	192	179	
2	267	70	267	---	70	286	289	70	---	217	213	
Inches												
1	8.12	1.81	8.62	9.12	1.81	9.12	9.12	1.81	6.81	7.56	7.06	
2	10.50	2.75	10.50	---	2.75	11.25	11.38	2.75	---	8.56	8.38	

[Close Section Above](#)

Table 8. Design D Dimensions

FLANGED VALVE SIZE, NPS	ASME						API				D—All Ratings		
	CL900 and 1500			CL2500			10,000 lb.						
	A		G	A		G	A			G	Stem Size		
	Raised Face	Ring-Type Joint		Raised Face	Ring-Type Joint		Spec A	Spec B	Spec C		9.5 (3/8)	12.7 (1/2)	19.1 (3/4)
mm													
1	254	254	46	308	308	54	---	---	---	---	173	192	179
2	308	311	70	391	394	83	364	397	360	83	---	217	213
Inches													
1	10.00	10.00	1.81	12.12	12.12	2.12	---	---	---	---	6.81 ⁽¹⁾	7.56 ⁽¹⁾	7.06 ⁽¹⁾
2	12.12	12.25	2.75	15.38	15.50	3.25	14.34	15.62	14.19	3.25	---	8.56	8.38

1. Not applicable for 10,000 lb. API.

[Close Section Above](#)

Table 9. Design D Dimensions

SCREWED VALVE SIZE, NPS	3600 psi		6000 psi and 9000 psi		D—All Ratings		
	A	G	A	G	3600 psi	6000 psi and 9000 psi	Stem Size
					9.5 (3/8)	12.7 (1/2)	19.1 (3/4)
mm							
1 ⁽¹⁾	168	46	197	54	172	192	178
2	229	70	267	83	---	216	211
Inches							
1 ⁽¹⁾	6.62	1.81	7.75	2.12	6.75	7.50	7.00
2	9.00	2.75	10.50	3.25	---	8.50	8.31

1. For 3600 psi and 6000 psi only.

[Close Section Above](#)

Table 10. Design DA Dimensions

FLANGED VALVE SIZE, NPS	A				D—All Ratings		
	ASME						
	CL300		CL600		Stem Size		
	Raised Face	Ring-Type Joint	Raised Face	Ring-Type Joint	9.5 (3/8)	12.7 (1/2)	19.1 (3/4)
mm							
1	109	116	116	116	135	154	141
2	155	164	165	167	---	164	159
Inches							
1	4.31	4.56	4.56	4.56	5.31	6.06	5.56
2	6.12	6.44	6.50	6.56	---	6.44	6.25

[Close Section Above](#)

Table 11. Design DA Dimensions

FLANGED VALVE SIZE, NPS	A							D—All Ratings		
	ASME				API					
	CL900 and 1500		CL2500		10,000 lb.			Stem Size		
	Raised Face	Ring-Type Joint	Raised Face	Ring-Type Joint	Spec A	Spec B	Spec C	9.5 (3/8)	12.7 (1/2)	19.1 (3/4)
mm										
1	127	127	154	154	---	---	---	135	154	141
2	178	179	195	197	182	198	180	---	164	159
Inches										
1	5.00	5.00	6.06	6.06	---	---	---	5.31	6.06	5.56
2	7.00	7.06	7.69	7.75	7.17	7.81	7.09	---	6.44	6.25

[Close Section Above](#)

Table 12. Design DA Dimensions

SCREWED VALVE SIZE, NPS	3600 psi		6000 psi and 9000 psi		D—All Ratings		
					Stem Size		
	A	G	A	G	9.5 (3/8)	12.7 (1/2)	19.1 (3/4)
mm							
1 ⁽¹⁾	76	89	89	102	133	152	140
2	102	124	114	130	---	162	157
Inches							
1 ⁽¹⁾	3.00	3.50	3.50	4.00	5.25	6.00	5.50
2	4.00	4.88	4.50	5.12	---	6.38	6.19

1. For 3600 psi and 6000 psi only.

[Close Section Above](#)

[Close Section Above](#)